



Castrol EDGE 5W-30 C3

Boosted with TITANIUM FST™ - Strength for Maximum Performance

Description

Advances in engine technology have led to increased power and efficiency, meaning engines work harder and under higher pressures than ever before.

The only thing keeping metal engine components apart is the oil, so it needs to be strong and remain strong.

Castrol EDGE is our strongest and most advanced range of engine oils. Its **TITANIUM FST™** doubles its film strength preventing oil film breakdown and reducing friction.

Castrol EDGE with **TITANIUM FST™**: helping your engine perform at its best.

Application

Castrol EDGE 5W-30 C3 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an API SN, ACEA C3 or earlier specification 5W-30 lubricant .

Castrol EDGE 5W-30 C3 is recommended and approved for use in vehicles from leading OEMs, please refer to the specifications section and your owners handbook.

*GM dexos2®: supersedes GM-LL-B-025 and GM-LL-A-025

Advantages

Castrol EDGE 5W-30 C3 gives you the confidence to demand maximum engine performance from today's modern, higher revving sports, performance and luxury vehicles requiring a high level of protection and higher performance low viscosity oils.

Castrol EDGE 5W-30 C3:

- Maximises short and long term engine performance
- Reduces engine deposits to help maximise engine response
- Delivers complete protection across a variety of engine speeds, conditions and temperatures
- Sustains maximum performance even when under pressure

Typical Characteristics

Name	Method	Units	Castrol EDGE 5W-30 C3
Density @ 15C, Relative	ASTM D4052	g/ml	0.8524
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	12.1
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	5750
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	70
Viscosity Index	ASTM D2270	None	173
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	204
Ash, Sulphated	ASTM D874	% wt	0.8

Product Performance Claims

ACEA C3
API SN/CF
BMW Longlife-04
dexos2®*
MB-Approval 229.31/ 229.51
Renault RN0700 / RN0710
VW 502 00/ 505 00/ 505 01

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE 5W-30 C3
26 Jul 2016
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com